

DOCUMENTATION TECHNIQUE

ÉMERILLON

Acier S355j2

Pièces estampées, bagues filetées et soudées

PETIT ŒIL

N°	Ø fil	D	P	Ø O	F	L	CMU en T	CR en T	PU en Kgs
0	7	17	18	12	62	76	0T15	0T75	0.080
0	8	18	20	13	72	89	0T235	1T175	0.130
0	10	25	25	15	85	105	0T35	1T75	0.250
1	12	29	32	17	104	130	0T6	3T	0.470
2	15	35	36	20	118	150	1T	5T	0.700
3	18	37	39	23	132	166	1T75	8T75	0.960
4	20	42	45	27	152	190	2T5	12T5	1.400
4B	22	47	50	32	172	216	3T3	16T5	2.000
5	25	54	57	35	192	240	4T	20T	2.930
5B	28	57	63	42	218	275	5T	25T	4.100
6	32	69	78	42	250	312	6T3	31T5	6.000



GRAND ŒIL

N°	Ø fil	D	P	Ø O	F	L	CMU en T	CR en T	PU en Kgs
0	10	25	25	23	90	110	0T35	1T75	0.250
1	12	29	32	32	126	152	0T6	3T	0.470
2	15	35	36	37	140	170	1T	5T	0.700
3	18	37	39	45	162	196	1T75	8T75	0.960
4	20	42	45	50	183	220	2T5	12T5	1.400
4B	22	47	50	53	200	240	3T3	16T5	2.000
5	25	54	57	58	222	270	4T	20T	2.930



Codification articles R. Rose

Émerillon	EM
Types	PO – Petit Œil GO – Grand Œil
Finition	G – Galva ou Zingué (selon Ø) N – Noir
Modèle	N°

Ex : Émerillon petit œil galva de 15
= EMPOG2